

DERWENT-ACC-NO: 2004-485244

DERWENT-WEEK: 200657

COPYRIGHT 2006 DERWENT INFORMATION LTD

TITLE: Durable press finishing method of cellulose products or cellulose products mixed with a little synthetic fiber

INVENTOR: KO, S W; KOH, S W

PATENT-ASSIGNEE: KO S W[KOSWI] , KOH S W[KOHSI]

PRIORITY-DATA: 2001KR-0077381 (December 7, 2001)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
PAGES MAIN-IPC		
KR 490256 B	May 17, 2005	N/A
000 D06M 013/00		
KR 2003047014 A	June 18, 2003	N/A
000 D06M 013/00		

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
APPL-DATE		
KR 490256B	N/A	2001KR-0077381
December 7, 2001		
KR 490256B	Previous Publ.	KR2003047014
N/A		
(KR2003047014A)	N/A	2001KR-0077381
December 7, 2001		

INT-CL (IPC): D06M013/00

ABSTRACTED-PUB-NO: KR2003047014A

BASIC-ABSTRACT:

NOVELTY - A durable press finishing method is characterized by adding a batching process or a steaming process. The durable press finishing method is capable of improving the lowering of physical properties and applying to cellulose products or cellulose products mixed with a little

synthetic fiber.

DETAILED DESCRIPTION - The durable pressing finishing method of the cellulose products or the cellulose products mixed with a little synthetic fiber is as follows: mixing 2-12% of a polymer former such as melamine formaldehyde, 2-12% of an N-methylol compound such as DMDHEU and 4-20% of a polycarboxylic acid crosslink agent such as BTCA, citric acid and malic acid; adding a catalyst, a softener, a permeating agent to the solution to produce a finishing solution; padding and batching(or steaming) with the finishing solution; and then heating and washing.

CHOSEN-DRAWING: Dwg.0/0

TITLE-TERMS: DURABLE PRESS FINISH METHOD CELLULOSE PRODUCT CELLULOSE PRODUCT

MIX SYNTHETIC

DERWENT-CLASS: A11 A21 A87 E17 F06

CPI-CODES: A03-A01A; A05-B02; A08-D01; A12-G; E07-D13B; E10-C02A; E10-C02F; F03-C04;

SECONDARY-ACC-NO:

CPI Secondary Accession Numbers: C2004-180819